

2.8 Pickup

FAT TRUCK[®]
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



Zeal Motor Inc.
101, rue de la Production
Cowansville, Quebec, Canada J2K 5H5
579.319.0060
sales@zealmotor.com
WWW.FATTRUCK.COM

2.8 Pickup

SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS	
Payload	2200 lb (1000 kg)	Make	Caterpillar	Front & Rear	FAT TRUCK® LGP 1640 x 640 x 610	Air conditioning	
Passengers capacity	2 + 6 optional	Model	C2.2 Turbo diesel	Pressure	0.5 to 4.5 PSI (0.07 to 0.31 BAR)	Front winch	
Maximum speed on land	25 mph (40 km/h)	Emission standards	EPA Tier 4 Final EU Stage V	Pressure control	Automatic pressure control	Additional battery	
Maximum speed on water	3.1 mph (5 km/h)	Number of cylinders	4 cylinders	FUEL SYSTEM		Rear Hitch	
Maximum uphill & downhill	35°/ 70%	Displacement	135 po³ (2.22 L)	Capacity	21 US Gal (80 L)	Front and rear shackles	
Maximum sidehill	22°/ 40%	Horsepower @ 2800 RPM	74 hp (55 kW)	Average fuel autonomy	12 h	Studs for ice	
Turning radius	0°	Torque @ 1400 RPM	199 lb-ft (270 N-m)	STANDARD EQUIPMENT		Engine & hydraulic heater 110 V	
Shipping weight	4960 lb (2250 kg)	Cooling System	Liquid cooled	Doors	Lockable	Canopy, 2-person cab	
Ground pressure fully loaded	1.6 lb/po² (0.11 kg/cm²)	ELECTRICAL		Operator seats	2 front seats with 3-points seat belts	Heater / defroster	
SAFETY FEATURES		Voltage	12 V	Lights	Front, brakes, position, flashers, dome	Front windshield with wiper	
ROPS	ISO 3471	Alternator capacity	275 A	Horn	Electric	Custom color	
EPA	Stage V	Battery capacity	960 CCA	Ingress	Front ladder with grab handles	Roof rack	
Brakes	Automatic safety brake	Battery type	AGM	Standard color	Red or white	Exterior mirrors	
DIMENSIONS		TRANSMISSION		Fire extinguisher	2.5 lb ABC	Back-up camera	
Height	103 in (2620 mm)	Type	Hydrostatic	OPERATOR & MAINTENANCE		Back-up alarm	
Length	146.5 in (3720 mm)	Final drive	Carbon fiber synchronous belts	Bilge pump		4-way camera system	
Width	100 in (2540 mm)	BRAKES		Lockable fuel cap		Rear ROPS	
Ground clearance	20.7 in (526 mm)	Brakes	Positive deceleration through hydrostatic transmission	Variable cooling fan for engine		Rear seats with safety belts	
CONTROLS		Parking brakes	Brake disc applied pressure released	Operator & Maintenance manual		Search light with remote control	
Controller	Microprocessor	WARRANTY		Limited 1 year / 1000 hours (Which ever comes first)			
Steering	Joystick						
Display	Color display						

