

8X8 Hauler

FAT TRUCK[®]
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



Zeal Motor Inc.
101, rue de la Production
Cowansville, Quebec, Canada J2K 5H5
579.319.0060
sales@zealmotor.com
WWW.FATTRUCK.COM

8X8 Hauler

SPECIFICATIONS

PERFORMANCE		ENGINE		FRONT CAR STANDARD EQUIPMENT		FRONT CAR OPTIONS	
Payload Front Car	1000 lb (452 kg)	Make	Cummins	Lockable doors		Custom cab colors	
Payload Rear Car	4000 lb (1810 kg)	Model	F3.8 Turbo diesel	Ladder, steps, grab handles		Air conditioning	
Passengers	4 front	Emission standards	EPA Tier 4 final EURO Stage V	2 x Seats with 3-points seat belts		Rear seats with seat belts	
Maximum speed on land	25 mph (40 km/h)	Number of cylinders	4 cylinders	Lights (LED): Front, brakes, position, flashers, dome		Bluetooth radio with speakers	
Maximum speed on water	3.1 mph (5 km/h)	Displacement	232 in ³ (3.8 L)	LED beacon lights		Side working LED lights	
Maximum uphill & downhill	35°/ 70%	Horsepower @ 2500 RPM	173 HP (129 kw)	Front LED bar		Searchlight with remote control	
Maximum sidehill	22°/ 40%	Torque @ 1500 RPM	457 lb-ft (620 N-m)	Electric Horn		2 x Front forward facing seat on the back	
Turning radius	24 ft (7.3 m)	Cooling System	Liquid cooled	Heater / Defroster		Electric front Winch 12 000 lb	
Basic vehicle weight	13 000 lb (5910 kg)			Back up camera 4 way camera system		Studded tires for ice	
Ground pressure loaded	1.9 psi (0.13 bar)			Electronic Inclinometer		110V AC engine block & hydraulic tank heater	
				Roof hatch		4 x Circulating fans	
SAFETY FEATURES		FUEL SYSTEM		FRONT CAR STANDARD EQUIPMENT		FRONT CAR OPTIONS	
ROPS	ISO 3471	Capacity	45 US Gal (170 L)	Brush guard		Cold weather package:	
Brakes	Automatic safety brake	Driving range	186 miles (300 km)	Exterior mirrors		Front 6000 BTU heater for feet	
		Average fuel autonomy	12 h	Lockable fuel cap		Rear diesel cab heater	
		Urea tank	8.33 US gal (31.5 L)	Bilge pump		Diesel coolant heater	
DIMENSIONS		POWERTRAIN		FRONT CAR STANDARD EQUIPMENT		REAR CAR STANDARD EQUIPMENT	
Height	111 in (2794 mm)	Type	Hydrostatic	Front bumper		LED stops, signals, backup lights	
Overall length	322 in (8179 mm)	Final drive	8 x Hydrostatic motors	4 x Sliding side windows		Bilge pump	
Width	100 in (2540 mm)			2 x D-rings		Backup alarm	
Ground clearance	25 in (635 mm)			Standard color: Red or White		Rear hitch	
				LED rear light bar		Tail gates with ladder	
CONTROLS		BRAKES		FRONT CAR STANDARD EQUIPMENT		REAR CAR STANDARD EQUIPMENT	
Controller	Microprocessor	Brakes	Positive deceleration through hydrostatic transmission	First aid kit		8 x Tie downs	
Steering	Joystick	Park brakes	Brake disc applied pressure released	Emergency Hammer		Wheel pods™	
Display	Rugged touch screen			Fire extinguisher 2.5 lb. ABC		2 x D-rings	
				Operator & Maintenance manual			
				Wheel pods™			
ELECTRICAL		TIRES		FRONT CAR STANDARD EQUIPMENT		REAR CAR OPTIONS	
Voltage	12 V	Front & Rear	FAT TRUCK® LGP			Fender tool box	
Alternator capacity	150 A	Pressure	1640 x 640 x 610			Exterior storage box	
Battery capacity	2 x 930 CCA	Pressure control	0.5 to 6 psi (0.07 to 0.41 bar)				
Battery type	AGM		Presets and variable pressure control				
						WARRANTY	
						Limited 1 year / 1000 hours (Which ever comes first)	

