

2.4 Pickup

FAT TRUCK[®]
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



Zeal Motor Inc.
101, rue de la Production
Cowansville, Quebec, Canada J2K 5H5
579.319.0060
sales@zealmotor.com
WWW.FATTRUCK.COM

2.4 Pickup

SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS	
Payload	2000 lb (905 kg)	Make	HATZ	Front & Rear	52 x 19 x 20 inches	Air conditioning	
Passenger capacity	4 (2 front + 2 rear)	Model	3H50TICD	Pressure	0.5 to 6 PSI (0.0035 to 0.42 kg/cm ²)	Front winch	
Maximum speed on land	20 mph (32 km/h)	Emission standards	EPA Tier 4 final EU Stage V	FUEL SYSTEM		Additional battery	
Maximum speed on water	3.1 mph (5 km/h)	Number of cylinders	3 cylinders	Capacity	19.5 US Gal (74 L)	Rear Hitch	
Maximum uphill & downhill	35°/ 70%	Displacement	89 cc ³ (1.46 L)	Average fuel autonomy	12 h	Front and rear shackles	
Maximum sidehill	22°/ 40%	Horsepower @ 2400 RPM	56 hp (42 kW)	STANDARD EQUIPMENT		Studs for ice	
Turning radius	0°	Torque @ 1600 RPM	136 lb-ft (184 N-m)	Doors	Front	Engine & hydraulic heater 110 V	
Base vehicle shipping weight	4200 lb (1900 kg)	Cooling System	Liquid cooled	Operator seats	2 front seats with 3-points seat belts	Canopy with openable windows, dome light	
Ground pressure fully loaded	2 lb/cc ² (0.14 kg/cm ²)	ELECTRICAL		Lights	Front, brakes, position, flashers, dome	Heater / defroster	
SAFETY FEATURES		Voltage	12 V	Horn	Electric	Extra heater	
ROPS	ISO 3471	Alternator capacity	110 A	Ingress	Ladders with grab handles	Front windshield with wiper	
EPA / Emission	Tier 4 Final/Stage V	Battery capacity	960 CCA	Standard color	Black	Custom color	
Brakes	Automatic safety brake	Battery type	AGM	Fire extinguisher	2.5 lb ABC	Front roof rack	
DIMENSIONS		TRANSMISSION		Bilge pump		Rear roof rack	
Height	91.5 in (2323 mm)	Type	Hydrostatic	First aid kit		Rear vinyl canopy	
Length	129 in (3283 mm)	BRAKES		Front and rear bumpers		Exterior mirrors	
Width	88 in (2236 mm)	Brakes	Positive deceleration through hydrostatic transmission	Lockable fuel cap		Back-up camera	
Ground clearance	18 in (457 mm)	Parking brakes	Brake disc applied, pressure released	Cup holders		Back-up alarm	
CONTROLS				Operator & Maintenance manual		4-Way camera system	
Controller	Microprocessor					Rear ROPS	
Steering	Joystick					Rear seats with safety belts	
Display	Color display					Directional light with remote control	
WARRANTY						Front, side and rear light LED bar	
Limited 1 year / 1000 hours (Which ever comes first)						LED strobe light	
						Electronic inclinometer	
						Cold weather package	
						Ventilation fan	
						Storage box	
						Rear tailgate with ladder	
						Tow package	
						High flotation tires and rim	
						Wheel Pods™	
						Transportation trailer	
						Transportation rack	
						Amphibious trailer	

