

## 2.4 Pickup

**FAT TRUCK**<sup>®</sup>  
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



**Zeal Motor Inc.**  
101, rue de la Production  
Cowansville, Quebec, Canada J2K 5H5  
579.319.0060  
sales@zealmotor.com  
[WWW.FATTRUCK.COM](http://WWW.FATTRUCK.COM)

# 2.4 Pickup

## SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS	
Payload	2000 lb (905 kg)	Make	HATZ	Front & Rear	52 x 19 x 20 inches	Front winch	
Passenger capacity	4 (2 front + 2 rear)	Model	3H50TICD	Pressure	0.5 to 6 PSI (0.0035 to 0.42 kg/cm <sup>2</sup> )	Additional battery	
Maximum speed on land	19 mph (30 km/h)	Number of cylinders	3 cylinders	<b>FUEL SYSTEM</b>		Rear Hitch	
Maximum speed on water	3.1 mph (5 km/h)	Displacement	89 cc <sup>3</sup> (1.46 L)	Capacity	19.5 US Gal (74 L)	Front and rear shackles	
Maximum uphill & downhill	35°/ 70%	Horsepower @ 2400 RPM	56 hp (42 kW)	Average fuel autonomy	12 h	Studs for ice	
Maximum sidehill	22°/ 40%	Torque @ 1600 RPM	136 lb-ft (184 N-m)	<b>STANDARD EQUIPMENT</b>		Engine & hydraulic heater 110 V	
Turning radius	0°	Cooling System	Liquid cooled	Doors	Front	Canopy with openable windows, dome light	
Base vehicle shipping weight	4200 lb (1900 kg)	<b>ELECTRICAL</b>		Operator seats	2 front seats with 3-points seat belts	Heater / defroster	
Ground pressure fully loaded	2 lb/pc <sup>2</sup> (0.14 kg/cm <sup>2</sup> )	Voltage	12 V	Lights	Front, brakes, position, flashers, dome	Extra heater	
<b>SAFETY FEATURES</b>		Alternator capacity	110 A	Horn	Electric	Front windshield with wiper	
ROPS	ISO 3471	Battery capacity	960 CCA	Ingress	Ladders with grab handles	Custom color	
EPA / Emission	Tier 4 Final/Stage V	Battery type	AGM	Standard color	Black	Front roof rack	
Brakes	Automatic safety brake	<b>TRANSMISSION</b>		Fire extinguisher	2.5 lb ABC	Rear roof rack	
<b>DIMENSIONS</b>		Type	Hydrostatic			Rear vinyl canopy	
Height	91.5 in (2323 mm)	<b>BRAKES</b>		Bilge pump		Exterior mirrors	
Length	129 in (3283 mm)	Brakes	Positive deceleration through hydrostatic transmission	First aid kit		Rear ROPS	
Width	88 in (2236 mm)	Parking brakes	Brake disc applied, pressure released	Front and rear bumpers		Rear seats with safety belts	
Ground clearance	20.6 in (523 mm)			Lockable fuel cap		Directional light with remote control	
<b>CONTROLS</b>				Cup holders		Front, side and rear light LED bar	
Controller	Microprocessor			Operator & Maintenance manual		LED strobe light	
Steering	Joystick					Electronic inclinometer	
Display	Color display					Cold weather package	
<b>WARRANTY</b>						Ventilation fan	
Limited 1 year / 1000 hours (Which ever comes first)						Storage box	
						Rear tailgate with ladder	
						Tow package	
						High flotation tires and rim	
						Wheel Pods™	
						Transportation trailer	
						Transportation rack	
						Amphibious trailer	

